



DN 2242 LH-AUT

## Global<sup>®</sup> DN 2200 AUT series - Two needle lockstitch machines

### TECHNICAL SPECIFICATIONS

Machine speed\*  
**up to 3500 spm**  
Oiling system  
**fully automatic**  
Number of needles  
**2**  
Needle gauge  
**standard 6.4 mm**  
Feed type  
**needle feed**  
Presser foot lift  
**max. 13 mm**  
Stitch length  
**max. 5 - 7 mm**  
Needle type  
**134 R**  
Stitch type  
**301**  
Electric presser foot lift  
**optional**

**DN 2242 AUT** - Double needle lockstitch with drop and needle feed. Machine is equipped with under bed thread trimmer and auto back tack (electric). Machine has vertical axis standard hooks.

**DN 2242 LH-AUT** - Same as DN 2242 AUT, but with large hooks.

**DN 2220 AUT** - Double needle lockstitch with drop and needle feed. The machine is equipped with under bed thread trimmer and has manually disengageable needle bars and auto back tack (electric). Machine has vertical axis standard hooks.

**DN 2220 LH-AUT** - Same as DN 2220 AUT, but with large hooks.

### MAQUINAS DE DOBLE AGUJA

**DN 2242 AUT** - Máquina de dos agujas, pespunte con arrastre por agujas y dientes. Esta equipada con corta-hilos y remate eléctrico. Garfio normal sobre eje vertical.

**DN 2242 LH-AUT** - La misma que la DN 2242 AUT, pero equipada con garfios grandes.

**DN 2220 AUT** - Máquina de dos agujas desembragable manual, pespunte con arrastre por agujas y dientes. Esta equipada con corta-hilos y remate eléctrico. Garfio normal sobre eje vertical.

**DN 2220 LH-AUT** - La misma que la DN 2220 AUT, pero equipada con garfios grandes.

### ZWEINADEL STEPPSTICHMASCHINEN

**DN 2242 AUT** - Zweinadel Steppstichmaschine mit Unter und Nadeltransport. Die Maschine ist mit Fadenabschneider und Verriegelungsautomatik (elektrisch) ausgestattet. Die Maschine hat einen normalen Vertikalgreifer.

**DN 2242 LH-AUT** - Baugleich mit DN 2242 AUT, jedoch mit grosser Greifer.

**DN 2220 AUT** - Zweinadel Steppstichmaschine mit Unter und Nadeltransport. Die Maschine ist mit ausschaltbarer Nadelstangen, Fadenabschneider und Verriegelungsautomatik (magnetisch) ausgestattet. Die Maschine hat einen normalen Vertikalgreifer.

**DN 2220 LH-AUT** - Baugleich mit DN 2220 AUT, jedoch mit grosser Greifer.

### MACHINE POINT NOUÉ A DEUX AIGUILLES

**DN 2242 AUT** - Machine deux aiguilles point noué, double entraînement par griffe et aiguille. Dispositif coupe fil et arrêts automatiques (électromagnétique). Crochets standards sur axe vertical.

**DN 2242 LH-AUT** - Machine identique à la DN 2242 AUT, mais avec crochets à grandes capacités.

**DN 2220 AUT** - Machine deux aiguilles point noué avec entraînement par griffe et aiguille.

Aiguilles escamotables à commande manuelle. Dispositif coupe fil et arrêts automatiques (électromagnétique). Crochets standards sur axe vertical.

**DN 2220 LH-AUT** - Machine identique à la DN 2220 AUT, mais avec crochets à grandes capacités.

## Global DN 2200 AUT series

Double needle, needle feed machines with thread trimmer and automatic back tack (all electric). These machines are high speed machines for light to heavy materials, like: shirts, jeans, jackets and other double needle work.















Disengageable needle bars.



Hooks with bobbin caps and thread trimming device.

### Specifications

 model	DN 2242 AUT	DN 2242 LH-AUT	DN 2220 AUT	DN 2220 LH-AUT
 number of needles	2	2	2	2
 Stitch length mm	5	5	5	5
 presser foot lift by hand (mm) by knee (mm)	7 13	7 13	7 13	7 13
 needle system	134 R	134 R	134 R	134 R
 space to right of needle (mm)	240	240	240	240
 max speed spm*	3500	2800	3200	2800
 manual split needle bar	—	—	•	•
 hooks	standard	large	standard	large
 electric presser foot lift	option	option	option	option
 thread wiper	•	—	•	—
 machine bed plate mm	518	518	518	518

★ Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL® Selection is brought to you by:

GLOBAL® is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:  
 1 machine model  
 2 part numbers